



G		Dielectric Strength		PARTS		MATERIALS		TREATMENT		AMOUNT	
Engagement force	≤25N	Rated voltage	>750V	A	HOUSING	PTFE	NATURAL COLOR			1	
Disengagement force	≥5N	Frequency Range	DC to 6 GHz	B	CONTACT	BRONZE	GOLD PLATED			1	
Retention	≥110N	Voltage standing wave ratio	<1.30 (DC-3GHz)	C	OUTER CONTACT	BRASS	NICKEL PLATED			1	
Mechanical lifespan	≥500	Insulation resistance	<1.40 (3GHz-6GHz)	D	SHIELD	BRASS	NICKEL PLATED			1	
IP rating	IP67/IP68	Contact resistance	≥1000mΩ	E	SHELL	PBT+GF	SPECIFY COLOR			1+1	
Operation Temperature	-40° C~105° C	Insertion Loss	<0.1x√f (GHz) dB	F							
RF Leakage	≥65 dB										

  

Dongguan Changjun Electronics Co., Ltd		TOLERANCE	
TITLE: FAKRA母头 线端直头 (长体) PART NO: CJ-FAKRA-Z-F01 SHEET: 1 / 1 SCALE: 1 : 1 DRAWN: Xie Wenjun CHECK: Long Jibang DATE: 2022-01-05		±0.05	.xxx
		±0.10	.xx
		±0.20	.x
		±0.30	ANG
DRAWING NO.: CJ-FAKRA0006		UNIT: mm	SCALE: REV A/0

由 Autodesk 教育版产品制作

由 Autodesk 教育版产品制作