



| PARTS | MATERIALS | TREATMENT | AMOUNT |
|---------------|-----------|-------------------|--------|
| A HOUSING | PBT+GF | BLACK | 1 |
| B CONTACT | BRONZE | BRIGHT TIN PLATED | 13 |
| C SHELL | BRASS | NICKL PLATED | 1 |
| D GROUND WIRE | BRONZE | NICKL PLATED | 1 |

| | | | |
|--|--|---|--|
| Engagement force ≤100N Rated voltage 30V | | Rated current 3A | |
| Disengagement force ≥35N Rated current ≥2000 | | Insulation resistance ≥1000MΩ | |
| Mechanical lifespan ≥2000 | | Contact resistance ≤10mΩ | |
| IP rating UL94 V-0 | | Operation Temperature -40° C~105° C | |
| Flammability | | | |

Dongguan Changjun Electronics Co., Ltd
 东莞市昌骏电子有限公司

标题: 13PIN圆形插头

| | | | |
|---|--|------------------------|--|
| TOLERANCE .xxx ±0.05 .xx ±0.10 .x ±0.20 x ±0.50 ANGLES ±1° | | TITLE: 13PIN圆形插头 | |
| PART NO: CJ-DJN13-01 | | DRAWING NO.: CJ-DJN005 | |
| SHEET: 1 / 1 | | SCALE: 1 : 1 | |
| DRAWN: Xie Wenjun | | CHECKS: Long Jibang | |
| DATE: 2022-01-05 | | SIZE: REV A/0 | |