



	PARTS	MATERIALS	TREATMENT	AMOUNT	
	A	HOUSING	PA66+GF	SPECIFY COLOR	1
	B	CONTACT	BRASS	GOLD PLATED	11
	C	NUT	BRASS	NICKL PLATED	1
	D				
	E				
	F				

Engagement force	$\leq 60\text{N}$	Rated volage	3PIN-60V 9PIN-30V
Disengagement force	$\geq 20\text{N}$	Rated current	3PIN-15A 9PIN-3A
Mechanical lifespan	≥ 500	Insulation resistance	$\geq 1000\text{M}\Omega$
IP rating	IP67/IP68	Contact resistance	$\leq 10\text{m}\Omega$
Flammability	UL94 V-0	Operation Temperature	$-40^{\circ}\text{C}\sim 105^{\circ}\text{C}$

Dongguan Junhao Interconnection Technology Co.,Ltd			
东莞市俊豪互联科技有限公司			
TOLERANCE		TITLE:	
.xxx	± 0.05	M16防水11P(3+8)线端公头+10.2L网纹螺丝	
.xx	± 0.10	PART NO:	DRAWING NO.:
.x	± 0.30	JH-M16CXB11-M01	CP-M160005
x	± 0.50	SHEET:	SCALE:
ANGLE	$\pm 1^{\circ}$	1 / 1	1 : 1
		UNIT:	SIZE:
		mm	A4
		CHECK:	DATE:
		Xie Wenjun	Long Jichang
			2023-02-10