



PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PA66+GF	GOLD PLATED	1
B CONTACT	BRASS	NICKEL PLATED	8
C NUT	BRASS	NICKEL PLATED	1
D O-RING	EPDM	BLACK	1

Dongguan Junhao Interconnection Technology Co., Ltd <b>东莞市俊豪互联科技有限公司</b>			
TITLE: H108 水密(4+4) 接插母头+10L 周接螺母		DRAWING NO.: CP-H160004	
PART NO:		SCALE: 1:1	
SHEET: 1 / 1		UNIT: mm	
DRAWN: Xie Wenjun		CHECK: Long Jichang	
DATE: 2022-04-07		SIZE: REV A/0	

Engagement force	Rated voltage	Rated current	Insulation resistance	Contact resistance	Operation Temperature
≤60N	4PTI-60V	4PTI-20A	4PTI-3A	≤10mΩ	-40° C~105° C
≥20N	Rated voltage	Rated current	Insulation resistance	Contact resistance	Operation Temperature
≥500	≥500	≥1000mA	≥1000MΩ	≤10mΩ	-40° C~105° C
IP rating	IP67/IP68	IP67/IP68	Contact resistance	Operation Temperature	-40° C~105° C
Flammability	UL94 V-0	UL94 V-0	Operation Temperature	-40° C~105° C	-40° C~105° C

由 Autodesk 教育版产品制作

由 Autodesk 教育版产品制作

1

2

3

4

5

6

7

8

1

2

3

4

5

6

7

8

A

A

B

B

C

C

F

F

G

G

H

H