



Engagement force	≤80N	Rated voltage	250V
Disengagement force	≥20N	Rated current	20A
Mechanical lifespan	≥500	Insulation resistance	≥1000M Ω
IP rating	IP67/IP68	Contact resistance	≤20m Ω
Flammability	UL94 V-0	Operation Temperature	-40° C~105° C

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PPS+GF	GOLD PLATED	1
B CONTACT	BRASS	NICKL PLATED	2+6
C OUTER CONTACT	BRASS	NICKL PLATED	1+1
D O-RING	EPDM	BLACK	1
E NUT	BRASS	NICKL PLATED	1

Dongguan Changjun Electronics Co., LTD  
**东莞市昌俊电子有限公司**

标题: M16防水IP(2+6) 线端母头(2+6) 5L六角直纹螺母

TOLERANCE	±0.05	TITLE:	M16防水IP(2+6) 线端母头(2+6) 5L六角直纹螺母
.xxx	±0.10	PART NO:	CJ-M16LX08-F02
.xx	±0.30	SHEET:	1 / 1
.x	±0.50	SCALE:	1 : 1
ANGLE	±1°	UNIT:	mm
		SIZE:	A4
		REV:	A/0
		DATE:	2023-09-14

DRAWN: Xie Wenjun  
 CHECK: Long Jichang