



Engagement force	≤40N	Rated voltage	24V
Disengagement force	≥10N	Rated current	2A
Mechanical lifespan	≥2000	Insulation resistance	≥1000MΩ
IP rating		Contact resistance	≤10mΩ
Flammability	UL94 V-0	Operation Temperature	-25° C~85° C

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PBT+GF	BLACK	1
B CONTACT	BRASS	NICKEL PLATED	7
C OUTER CONTACT	BRASS	GOLD PLATED	1
D GROUND WIRE	BRONZE	BRIGHT TIN PLATED	1
E		NICKEL PLATED	
F			

Dongguan Changjun Electronics Co., Ltd
东莞市昌骏电子有限公司

TITLE: mini DIN 7P线端插头(保特)

PART NO: CJ-AD7P-F01
 DRAWING NO.: CJ-1000026

SHEET: 1 / 1
 SCALE: 1 : 1
 UNIT: mm
 SIZE: A4
 REV: A/0

TOLERANCE
 .xxx ±0.05
 .xx ±0.10
 .x ±0.20
 ANGLES ± 1°

DRAWN: Xie Kunjun
 CHECKS: Long Jichang
 DATE: 2022-01-05