



A	3pin	4pin	5pin	6pin
B	图形			
C				
D				
E				
F				
G				
H				
I				
	Engagement force	$\leq 60N$	Rated voltage	250V
	Disengagement force	$\geq 20N$	Rated current	20A
	Mechanical lifespan	$\geq 500$	Insulation resistance	$\geq 1000M \Omega$
	IP rating	IP67/IP68	Contact resistance	$\leq 20m \Omega$
	Flammability	UL94 V-0	Operation Temperature	$-40^{\circ}C \sim 105^{\circ}C$

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PA66+GF	SPECIFY COLOR	1
B CONTACT	BRASS	GOLD PLATED	3~6
C NUT	BRASS PA66+GF	NICKL PLATED BLACK	2
D OUTER CONTACT	BRASS	NICKL PLATED	1
E O-RING	EPDM	BLACK	3
F SHIELD	BRASS	NICKL PLATED	1

**Dongguan Changjun Electronics Co., LTD**  
**东莞市昌俊电子有限公司**

**7/8-16UN2A防水30°接触公头(五金组装式款)**

TITLE:			
PART NO:	CJ-M23AH(3°)-M12		
DRAWING NO.:	CP-M230027		
SHEET:	1 / 1	SCALE:	1 : 1
DRAWN:	Xie Wenjun	CHECK:	Long Jichang
DATE:	2022-05-27		

TOLERANCE:  $\pm 0.05$   
 $\pm 0.10$   
 $\pm 0.30$   
 $\pm 0.50$   
 ANGLE:  $\pm 1^{\circ}$