



	1	2	3	4	5	6	7	8
Engagement force	$\leq 60N$	Rated voltage	250V					
Disengagement force	$\geq 20N$	Rated current	20A					
Mechanical lifespan	≥ 500	Insulation resistance	$\geq 1000M \Omega$					
IP rating	IP67/IP68	Contact resistance	$\leq 20m \Omega$					
Flammability	UL94 V-0	Operation Temperature	$-40^{\circ}C \sim 105^{\circ}C$					

	A	B	C	D	E	F
PARTS	HOUSING	CONTACT	CONTACT	OUTER CONTACT	0-RING	SHIELD
MATERIALS	PA66+GF	BRASS	BRASS PA66+GF	BRASS	EPDM	BRASS
TREATMENT	SPECIFY COLOR	GOLD PLATED	NICKL PLATED BLACK	NICKL PLATED	BLACK	NICKL PLATED
AMOUNT	1	3~6	2	1	3	1

东莞市昌骏电子有限公司
Dongguan Changjun Electronics Co., LTD

7/8-16UN2A防水30线端子头(压金组装式)

TITLE: 7/8-16UN2A防水30线端子头(压金组装式)

PART NO: CJ-M23AH(30)-F12

SHEET: 1 / 1

SCALE: 1 : 1

DRAWING NO.: CP-M230029

UNIT: mm

SIZE: A4

REV: A/0

DRAWN: Xie Wenjun

CHECK: Long Jichang

DATE: 2023-09-14